



GUARANTEED
QUALITY



WORK &
PROFESSIONAL

At Ledlenser, we pride ourselves in superior quality in everything we do. From design all the way to manufacturing our product, we push the boundaries of innovation every step of the way.

All Ledlenser lights purchased from an authorized reseller are backed by a five-year warranty. An additional two years can be added to this warranty – seven years in total – if the user registers their product. Each light comes with a product registration card and unique product code. The user can simply scan the included QR code on the product registration card and follow the prompted instructions or enter the URL on a web browser. Once the product information has been entered on our website, the warranty becomes a full seven-year warranty.

7
YEAR
WARRANTY*



THERE IS MORE!
Follow the QR code
to our full line product catalog.



GERMAN ENGINEERING
& DESIGN

NEW
CORE, WORK
& SIGNATURE
LIGHTS

The information pertaining to package contents, appearance, performance, dimensions and weight corresponds to the information available at the time of publication. In the interest of product development, we reserve the right to change package contents, appearance, design and color without prior notice. Product images may vary from the actual products and may show optional accessories which can be purchased separately. Errors and misprints excepted.

1) Measurements according to ANSI FL1 in the respective setting. If no setting is explicitly named for a measured value, the values for luminous flux (lumens/lm) and luminous range (meters/m) refer to the brightest setting and the values for the luminous period (hours/h) refer to the lowest setting. For „max. - min.“ range, in terms of luminous flux (lumens/lm) and luminous range (meters/m), the range from the brightest setting (first value) to the lowest setting (second value) is given. With regards to the values of the luminous period (hours/h), the range from the lowest setting (first value) to the brightest setting (second value) is given. A boost function (if available) can be used several times, but only for short periods. If the lamp has different energy modes, measurement is based on „energy-saving mode.“

2) Charging time (in hours and minutes) may vary by power supply.

*) Ledlenser has a non-transferable warranty. Ledlenser's warranty is conveyable to the end-use purchaser only through authorized Dealers and Distributors. No other warranty is expressed, implied or valid when purchased from an unauthorized third party. Five year warranty from the date of purchase, or seven years with online registration through our website. The warranty applies worldwide; legal warranty rights also apply. It covers defects in material and manufacture. Battery packs are guaranteed to work correctly for 24 months. This warranty does not cover products in the "Solidline" series, Ledlenser K1 and Ledlenser K2, as well as defective batteries, holsters, pouches, remote switches, color filters, imprints and surface coatings. The warrantor is Ledlenser GmbH & Co. KG, Kronenstr. 5-7, 42699 Solingen, Germany. For more information visit ledlenserusa.com/pages/service-warranty

Ledlenser USA
80 SE Madison #130
Portland, OR 97214

ledlenserusa.com

@ledlenserusa
@ledlenseramericas

Item no. 880627

POWERUP

GET THE JOB DONE
ACCOMPLISH MORE
TAKE PRIDE



P-SERIES CORE NEW



LED	P2R CORE	P4R CORE	P5R CORE
Luminous flux ¹ (lm)	120 / 50 / 15	200 / 90 / 15	500 / 350 / 130 / 15
Beam Distance ¹ (m)	65 / 45 / 15	90 / 60 / 15	250 / 180 / 110 / 40
Run Time ¹ (h)	0.5 / 1 / 5	1.5 / 3 / 25	- / 1 / 3.5 / 25
Battery	1x Li-ion Battery 3.7V with Mikro-USB	1x Li-ion Battery 3.7V with Mikro-USB	1x 14500 Li-ion Battery 3.7V
Rechargeable	Yes	Yes	Yes
TECHNOLOGY			
Smart Light Technology			●
Magnetic Charge System			●
Advanced Focus System	●	●	●
ITEM NO.	880513	880514	880515



LED	P6R CORE	P7R CORE	P17R CORE	P6R CORE QC
Luminous flux ¹ (lm)	900 / 600 / 240 / 15	1400 / 1000 / 440 / 15	1200 / 900 / 350 / 15	270 / 120 / 15
Beam Distance ¹ (m)	240 / 190 / 120 / 25	300 / 210 / 130 / 15	560 / 420 / 270 / 50	335 / 220 / 80
Run Time ¹ (h)	- / 2 / 6 / 95	- / 2 / 4 / 90	- / 2.75 / 12 / 200	5 / 14 / 110
Battery	1x18650 Li-ion Battery 3.7V	1x 21700 Li-ion Battery 3.7V	1x LiFePO4 Battery pack 6.4V	1x Li-ion Battery pack 3.7V
Rechargeable	Yes	Yes	Yes	Yes
TECHNOLOGY				
Smart Light Technology	●	●	●	
Magnetic Charge System	●	●		
Advanced Focus System	●	●	●	●
ITEM NO.	880516	880518	880512	880620

P-SERIES CLASSIC



LED	P2	P3	P4
Luminous flux ¹ (lm)	16	25	18
Beam Distance ¹ (m)	25	60	25
Run Time ¹ (h)	7	6	8.5
Battery	1x (AAA) Alkaline 1.5V	1x (AAA) Alkaline 1.5V	2x (AAA) Alkaline 1.5V
Rechargeable	No	No	No
TECHNOLOGY			
Rapid Focus		●	
Advanced Focus System	●	●	●
Floating Charge System			
ITEM NO.	880046 (Box), 880045 (Blister)	880017 (Blister)	880048 (Box), 880047 (Blister)



LED	P5	P5R	P7	P7R
Luminous flux ¹ (lm)	140	420 / 20	450 / 250 / 40	1000 / 250 / 20
Beam Distance ¹ (m)	120	240 / 50	300 / 220 / 100	300 / 150 / 40
Run Time ¹ (h)	4	3 / 15	1 / 2 / 25	2 / 5 / 40
Battery	1x (AA) Alkaline 1.5V	1x 14500 Li-ion Battery 3.7V	4x (AAA) Alkaline 1.5V	1x 18650 Li-ion Battery 3.7V
Rechargeable	No	Yes	No	Yes
TECHNOLOGY				
Rapid Focus	●	●	●	●
Advanced Focus System	●	●	●	●
Floating Charge System		●		●
ITEM NO.	880012 (Box), 880011 (Blister)	880014 (Box), 880116 (Blister)	880004 (Box), 880003 (Blister)	880358 (Box), 880555 (Blister)

¹⁻² Information on back cover

T-SERIES CLASSIC



LED	TT	T ²	T ² QC
Luminous flux ¹ (lm)	280 / 25	240 / 25	140
Beam Distance ¹ (m)	220 / 80	180 / 60	25
Run Time ¹ (h)	3 / 25	4 / 25	4
Battery	3x (AAA) Alkaline 1.5V	3x (AAA) Alkaline 1.5V	3x (AAA) Alkaline 1.5V
Rechargeable	No	No	No
TECHNOLOGY			
Temperature Control	●		
Rapid Focus			
Advanced Focus System	●		
ITEM NO.	880227 (Box), 880226 (Blister)	880229 (Box), 880229 (Blister)	880292 (Blister)

¹⁻⁷ Information on back cover

THE ULTIMATE HAND-HELD SEARCHLIGHT

X21R



LED	
Luminous flux ¹ (lm)	5000 / 3500 / 200
Beam Distance ¹ (m)	800 / 700 / 150
Run Time ¹ (h)	- / 5 / 40
Battery	1x LiFePO4 Battery pack 9,6V
Rechargeable	Yes
TECHNOLOGY	
Smart Light Technology	●
Floating Charge System	●
Emergency Light	●
ITEM NO.	501967



i-SERIES



i4

LED	
Luminous flux ¹ (lm)	120 / 10
Beam Distance ¹ (m)	80 / 20
Run Time ¹ (h)	4 / 20
Battery	2x (AAA) Alkaline 1.5V
Rechargeable	No
TECHNOLOGY	
Advanced Focus System	●
ITEM NO.	880386

K-SERIES

NEW



K4R

K6R

K6R Safety

LED			
Luminous flux ¹ (lm)	120 / 80 / 20	400 / 200 / 20	400 / 200 / 20
Beam Distance ¹ (m)	30 / 25 / 10	80 / 50 / 15	80 / 50 / 15
Run Time ¹ (h)	- / 1 / 3.5	- / 1.5 / 10	- / 1.5 / 8
Battery	1x Li-ion Battery 3.7V	1x Li-ion Battery 3.7V	1x Li-ion Battery 3.7V
Rechargeable	Yes	Yes	Yes
FEATURES			
	Transportation Lock	Transportation Lock, Red light	Transportation Lock, Alarm
ITEM NO.	502574 (gray), 502575 (rose)	502577 (gray), 502578 (rose)	502580 (gray), 502581 (rose)

PENLIGHT.
COMPACT.
HANDY.

P-SERIES WORK NEW



LED	P2R WORK	P4R WORK	P5R WORK
Luminous flux ¹ (lm)	110 / 50 / 15	170 / 70 / 15	480 / 320 / 120 / 15
Beam Distance ¹ (m)	90 / 60 / 20	100 / 65 / 20	240 / 165 / 100 / 30
Run Time ¹ (h)	0.5 / 1.5 / 7	1.25 / 3 / 15	- / 1 / 3 / 25
Battery	1x Li-ion Batterypack 3.7V	1x Li-ion Batterypack 3.7V	1x 14500 Li-ion Battery 3.7V
Rechargeable	Yes	Yes	Yes
TECHNOLOGY			
Smart Light Technology			●
Magnetic Charge System	●	●	●
Advanced Focus System	●	●	●
ITEM NO.	880526	880527	880528

¹⁻⁷ Information on back cover



LED	P6R WORK	P7R WORK	P18R WORK
Luminous flux ¹ (lm)	850 / 700 / 300 / 15	1200 / 900 / 390 / 15	4500 / 2600 / 1000 / 30
Beam Distance ¹ (m)	230 / 190 / 115 / 20	240 / 180 / 115 / 15	720 / 420 / 260 / 50
Run Time ¹ (h)	- / 1.5 / 2.5 / 45	- / 2 / 3.25 / 60	- / 2.5 / 4.5 / 70
Battery	1x 18650 Li-ion Battery 3.6V	1x 21700 Li-ion Battery 3.7V	1x Li-ion Batterypack 11.1V
Rechargeable	Yes	Yes	Yes
TECHNOLOGY			
Smart Light Technology	●	●	●
Flex Sealing Technology	●	●	
Natural Light	●	●	
ITEM NO.	880529	880530	880525

P-SERIES WORK
HIGH-PERFORMANCE
POWER PACKS



P-SERIES SIGNATURE NEW



LED	P6R SIGNATURE	P7R SIGNATURE	P18R SIGNATURE
Luminous flux ¹ (lm)	1400 / 1100 / 450 / 15	2000 / 1200 / 500 / 15	4500 / 2600 / 1000 / 30
Beam Distance ¹ (m)	240 / 190 / 110 / 20	330 / 200 / 130 / 20	720 / 420 / 260 / 50
Run Time ¹ (h)	- / 1.25 / 2.5 / 60	- / 2 / 3.25 / 90	- / 2.5 / 4.5 / 70
Battery	1x 18650 Li-ion Battery 3.6V	1x 21700 Li-ion Battery 3.7V	1x Li-ion Batterypack 11.1V
Rechargeable	Yes	Yes	Yes
TECHNOLOGY			
Smart Light Technology	●	●	●
Flex Sealing Technology	●	●	
Magnetic Charge System	●	●	●
ITEM NO.	880521	880523	880519

H-SERIES CORE

NEW



H5 CORE



H5R CORE



LED		
☀ Luminous flux ¹ (lm)	350 / 200 / 15	500 / 300 / 15
☞ Beam Distance ¹ (m)	160 / 120 / 30	200 / 150 / 30
🕒 Run Time ¹ (h)	- / 2 / 20	- / 2 / 50
🔋 Battery	2x (AA) Alkaline 1.5V	1x Li-ion Batterypack 3.7V
🔌 Rechargeable	No	Yes
TECHNOLOGY		
⚙ Flex Sealing Technology	●	●
🧲 Magnetic Charge System		●
🔊 Advanced Focus System	●	●
ITEM NO.	880504	880505

¹⁻⁷ Information on back cover



H7R CORE



H15R CORE



H19R CORE



☀ Luminous flux ¹ (lm)	1000 / 600 / 15	2500 / 1000 / 20	3500 / 1600 / 800 / 200
☞ Beam Distance ¹ (m)	250 / 200 / 25	250 / 170 / 20	300 / 230 / 150 / 80
🕒 Run Time ¹ (h)	- / 4 / 65	- / 5 / 80	- / 4 / 7 / 20
🔋 Battery	1x 21700 Li-ion Battery 3.7V	1x Li-ion Batterypack 7.4V	1x Li-ion Batterypack 7.4V
🔌 Rechargeable	Yes	Yes	Yes
TECHNOLOGY			
⚙ Flex Sealing Technology	●	●	
🧲 Magnetic Charge System	●	●	●
🔊 Advanced Focus System	●	●	
ITEM NO.	880506	880502	880503

THE NEW H-SERIES
POWERFUL ENLIGHTENMENT



H-SERIES CLASSIC



H3.2

H4

H4R

LED			
☀ Luminous flux ¹ (lm)	120 / 5	250 / 150 / 20	250 / 150 / 20
↔ Beam Distance ¹ (m)	100 / 20	35 / 25 / 10	35 / 25 / 10
🕒 Run Time ¹ (h)	6 / 60	- / 3 / 40	- / 3 / 40
🔋 Battery	3x (AAA) Alkaline 1.5V	3x (AAA) Alkaline 1.5V	1x LiPo Batterypack 3.7V
🔌 Rechargeable	No	No	Yes
TECHNOLOGY			
🔊 Smart Light Technology			
🌡 Temperature Control		●	●
🎯 Advanced Focus System	●		
ITEM NO. (box)	880564	880477	880475



H7.2

H7R.2

H8R

H14R.2

LED				
☀ Luminous flux ¹ (lm)	250 / 200 / 20	300 / 200 / 20	600 / 250 / 10	1000 / 450 / 60
↔ Beam Distance ¹ (m)	160 / 140 / 50	160 / 140 / 50	150 / 100 / 20	300 / 200 / 70
🕒 Run Time ¹ (h)	5 / 8 / 30	4 / 10 / 30	10 / 15 / 120	6 / 12 / 35
🔋 Battery	4x (AAA) Alkaline 1.5V	1x LiPo Battery 3.7V	1x 18650 Li-ion Battery 3.6V	1x Li-ion Battery 3.7V
🔌 Rechargeable	No	Yes	Yes	Yes
TECHNOLOGY				
●	●	●	●	●
●	●	●	●	●
●	●	●	●	●
880002 (Box), 880001 (Blister)	880022 (Box), 880021 (Blister)	880501 (Box), 880500 (Blister)	880036 (Box)	



FREE HANDS.
PERFECT ILLUMINATION.
PROVEN QUALITY.



SEO7R

LED	
☀ Luminous flux ¹ (lm)	220 / 20
↔ Beam Distance ¹ (m)	130 / 40
🕒 Run Time ¹ (h)	5 / 20
🔋 Battery	1x Li-ion Batterypack 3.7V
🔌 Rechargeable	Yes
TECHNOLOGY	
🎯 Rapid Focus	●
🔊 Smart Light Technology	●
🌡 Optisense Technology	●
ITEM NO.	
Item no. Box	6007-RB (Black) Box
Item no. Test-it-Blister	880305 (Blue) Box



^{1,2} Information on back cover

H-SERIES WORK NEW



LED	H5R WORK	H7R WORK	H15R WORK
Luminous flux ¹ (lm)	500 / 300 / 15	1000 / 600 / 15	2500 / 1000 / 20
Beam Distance ¹ (m)	200 / 150 / 30	250 / 200 / 25	250 / 170 / 20
Run Time ¹ (h)	- / 2 / 45	- / 4 / 60	- / 4 / 70
Battery	1x Li-ion Batterypack 3.7V	1x 21700 Li-ion Battery 3.7V	1x Li-ion Batterypack 7.4V
Rechargeable	Yes	Yes	Yes
TECHNOLOGY			
Flex Sealing Technology	●	●	●
Magnetic Charge System	●	●	●
Advanced Focus System	●	●	●
ITEM NO.	880510	880511	880509



LED	iH9R	iH11R
Luminous flux ¹ (lm)	600 / 400 / 170 / 20	1000 / 750 / 300 / 10
Beam Distance ¹ (m)	200 / 180 / 120 / 40	320 / 300 / 200 / 30
Run Time ¹ (h)	- / 7 / 10 / 60	- / 4 / 8 / 100
Battery	1x Li-ion Batterypack 3.7V	1x 18650 Li-ion Battery 3.6V
Rechargeable	Yes	Yes
TECHNOLOGY		
Magnetic Charge System	●	●
Dual Power Source	●	
Advanced Focus System	●	●
ITEM NO.	502023	502022

iH-SERIES



LED	iH5	iH5R	iH8R
Luminous flux ¹ (lm)	200 / 20	400 / 20	600 / 10
Beam Distance ¹ (m)	130 / 40	180 / 40	180 / 20
Run Time ¹ (h)	4.5 / 35	4 / 35	10 / 120
Battery	1x (AA) Alkaline 1.5V	1x 14500 Li-ion Battery 3.7V	1x 18650 Li-ion Battery 3.7V
Rechargeable	No	Yes	Yes
TECHNOLOGY			
Magnetic Charge System		●	
Smart Light Technology	●	●	●
Dual Power Source	●	●	
ITEM NO.	502024	502025	880427

H-SERIES SIGNATURE



LED	H7R SIGNATURE	H19R SIGNATURE
Luminous flux ¹ (lm)	1200 / 700 / 15	4000 / 1800 / 800 / 200
Beam Distance ¹ (m)	260 / 220 / 25	330 / 250 / 150 / 80
Run Time ¹ (h)	- / 3.5 / 65	- / 3.5 / 7 / 20
Battery	1x 21700 Li-ion Battery 3.7V	1x Li-ion Batterypack 7.4V
Rechargeable	Yes	Yes
TECHNOLOGY		
Magnetic Charge System	●	●
Temperature Control	●	●
Advanced Focus System	●	
ITEM NO.	880508	880507

¹⁻² Information on back cover

WORK & FLOOD LIGHTS



LED	iW2R	iW2R laser	iW3R
Luminous flux Flood ¹ (lm)	150 / 75	150 / 75	-
Run Time Flood ¹ (h)	1.5 / 3	1.5 / 3	-
Luminous flux Spot ¹ (lm)	100	Laser <1mW	320 / 30
Run Time Spot ¹ (h)	1.5	-	3.5 / 40
Battery	Li-ion Battery 3.7V (internal)	Li-ion Battery 3.7V (internal)	Li-ion Battery 3.7V (internal)
Rechargeable	Yes	Yes	Yes
FEATURES	<ul style="list-style-type: none"> • 2-in-1 function: COB LED for wide flat illumination and spot LED for focused light • Pen lamp: Rectangular, to the • Rounded metal housing with ruler function • Clip for attaching the lamp on the breast pocket 	<ul style="list-style-type: none"> • 2-in-1 function: laser pointer and COB-LED for wide area illumination • Pen lamp: Rectangular, to the • Rounded metal housing with ruler function • Clip for attaching the lamp on the breast pocket 	<ul style="list-style-type: none"> • Power bank with 4000 mAh battery capacity • Flashlight with spotlight • Battery and Charge indicator • Two dimming levels • Covered connections, dust and water protected with IP54 rating
ITEM NO.	502082	502083	502173



LED	iW4R	iW5R flex	iW5R	iW7R
Luminous flux Flood ¹ (lm)	150 / 75	600 / 250	300 / 125	600 / 250
Run Time Flood ¹ (h)	2 / 4	2 / 4	3 / 6	2 / 4
Luminous flux Spot ¹ (lm)	75	100	300	300
Run Time Spot ¹ (h)	2	6.5	2.5	3
Battery	Li-ion Battery 3.7V (internal)	Li-ion Battery 3.7V (internal)	Li-ion Battery 3.7V (internal)	Li-ion Battery 3.7V (internal)
Rechargeable	Yes	Yes	Yes	Yes
FEATURES	<ul style="list-style-type: none"> • Tilt mechanism for flexible align • 2 light sources (spot and flood) • Mounting magnet • Battery level indicator • Charge indicator 	<ul style="list-style-type: none"> • Fold-out lamp head • 2 light sources (spot and flood) • Hook and mounting magnet • Battery level indicator • Charge indicator 	<ul style="list-style-type: none"> • 2 light sources (spot and flood) • Hook with tilt mechanism and mounting magnet • Charging via USB cable • Battery level indicator • Charge indicator 	<ul style="list-style-type: none"> • Charging via charging station • 2 light sources (spot and flood) • Hook with tilt mechanism and mounting magnet • Battery level indicator • Charge indicator
ITEM NO.	502003	502006	502004	502005

^{1,2} Information on back cover



LED	iF2R	iF3R
Luminous flux Flood ¹ (lm)	200 / 100	1000 / 750 / 500 / 250 / 100
Run Time Flood ¹ (h)	3 / 6	1.5 / 2 / 3 / 5 / 15
Luminous flux Spot ¹ (lm)	75	-
Run Time Spot ¹ (h)	4	-
Battery	Li-ion Battery 3.7V (internal)	Li-ion Battery 3.7V (internal)
Rechargeable	Yes	Yes
FEATURES	<ul style="list-style-type: none"> • Flexible attachment and alignment thanks to the movable stand, Magnet and hook • Three light levels (2x flood, 1x spot) 	<ul style="list-style-type: none"> • Flexible attachment and alignment thanks to the movable stand, magnet and hook • Five levels of light
ITEM NO.	502170	502171



LED	iF4R	iF4R music	iF8R
Luminous flux Flood ¹ (lm)	2500 / 1500 / 1000 / 500 / 200	2500 / 1500 / 1000 / 500 / 200	4500 / 3000 / 2000 / 1000 / 400
Run Time Flood ¹ (h)	1.3 / 2 / 3 / 6 / 15	1.3 / 2 / 3 / 6 / 15	1.25 / 1.5 / 2.5 / 5 / 12
Battery	Li-ion Battery 3.7V (internal)	Li-ion Battery 3.7V (internal)	Li-ion Battery 3.7V (internal)
Rechargeable	Yes	Yes	Yes
TECHNOLOGY	<ul style="list-style-type: none"> • Magnetic Charge System • Powerbank-Funktion • Cooling Technology 	<ul style="list-style-type: none"> • Bluetooth 	<ul style="list-style-type: none"> • NEW
ITEM NO.	502001	502172	502002

I.S. FLASHLIGHTS Ex



LED	EX4	EX7	EX7R
Luminous flux ¹ (lm)	50	200 / 60	220 / 50
Beam Distance ¹ (m)	35	120 / 70	140 / 65
Run Time ¹ (h)	7	16 / 45	10 / 45
Battery	2x (AAA) Alkaline 1.5V	3x (AA) Alkaline 1.5V	1x Li-ion Batterypack 3.7V
Rechargeable	No	No	Yes
TECHNOLOGY			
Advanced Focus System		●	●
ITEM NO.	880428	880429	880431

^{1,2} Information on back cover

iL-FLASHLIGHTS



LED	iL4	iL7	iL7R
Luminous flux ¹ (lm)	80	340 / 70	360 / 55
Beam Distance ¹ (m)	50	165 / 80	170 / 70
Run Time ¹ (h)	4	7 / 37	6 / 40
Battery	2x (AAA) Alkaline 1.5V	3x (AA) Alkaline 1.5V	1x Li-ion Batterypack 3.7V
Rechargeable	No	No	Yes
TECHNOLOGY			
Advanced Focus System		●	●
ITEM NO.	880433	880434	880436

LANTERN



LED	iA6R
Luminous flux Flood ¹ (lm)	750 / 550 / 20
Beam Distance ¹ (m)	-
Run Time ¹ (h)	- / 4 / 70
Battery	1x 18650 Li-ion Battery 3.6V
Rechargeable	Yes
TECHNOLOGY	
Smart Light Technology	●
Micro Prism Technology	●
Powerbank-Funktion	●
ITEM NO.	501962

GLARE-FREE
WORK LIGHT

TECHNOLOGY PROVIDES
THE ADVANTAGE

I.S. HEADLAMPS



EXH8



EXH8R



LED		
☀ Luminous flux ¹ (lm)	180 / 50	200 / 45
➡ Beam Distance ¹ (m)	120 / 65	130 / 60
🕒 Run Time ¹ (h)	15 / 40	10 / 45
🔋 Battery	3x (AA) Alkaline 1.5V	1x Li-ion Battery pack 3.7V
🔌 Rechargeable	No	Yes
TECHNOLOGY		
🔍 Advanced Focus System	●	●
ITEM NO.	880430	880432

iL-HEADLAMPS



iLH8



iLH8R



LED		
☀ Luminous flux ¹ (lm)	280 / 60	300 / 50
➡ Beam Distance ¹ (m)	160 / 80	160 / 70
🕒 Run Time ¹ (h)	9 / 38	7 / 40
🔋 Battery	3x (AA) Alkaline 1.5V	1x Li-ion Battery pack 3.7V
🔌 Rechargeable	No	Yes
TECHNOLOGY		
🔍 Advanced Focus System	●	●
ITEM NO.	880435	880437

¹⁻² Information on back cover

FLEX-SERIES

Portable Energy



FLEX3



FLEX7

TECHNICAL SPECS	Powerbank+	Powerbank+
➦ Length (mm / in)	109 / 4.3	109 / 4.3
⚖ Weight with battery (g / oz)	88 / 3.1	164 / 5.8
TECHNOLOGY		
🔋 Battery	1x 18650 Li-ion Battery 3.6V	2x 18650 Li-ion Battery 3.6V
🔌 Rechargeable	Yes	Yes
FEATURES		
	6-IN-1	6-IN-1
	1. Water and dust protection (IP65) 2. Battery charger 3. Double protection against short circuit (box and battery) 4. Charge level indicator for the battery	1. Water and dust protection (IP65) 2. Battery charger 3. Double protection against short circuit (box and battery) 4. Charge level indicator for both batteries
MATCHES		
Ledlenser lights	iH11R, MH11, MH10, NEO10R, ML6, ML6 Warm Light, ML6 Connect WL, P6R Core, P6R Signature, P6R Work	iH11R, MH11, MH10, NEO10R, ML6, ML6 Warm Light, ML6 Connect WL, P6R Core, P6R Signature, P6R Work
ITEM NO.	880553	880554



POWERBANK –
INNOVATIVE
PORTABLE POWER